



CE

Thermospandy

CUSTOMIZED TANKS FOR CARRYING
AND SPRAYING ASPHALT EMULSION



Thermospandy

Veneta Tecnologie's asphalt emulsion tanks are tailored to the customer's requirements. There is an extensive range of systems available, either for loading and transporting on trucks or, alternatively, permanently mounted and type approved for road use. Standard capacities range from 500 to 5,000 litres while

larger capacities are available on request. The heated tank ensures that the emulsion is kept at just the right temperature. All Veneta Tecnologie tanks are made in conformity with EC machinery directive 89/392.



Main features:

The following items are meant as examples only. Refer to the price list for details of the features pertaining to each model.

HOLDING TANK fitted with top manhole for emulsion filling. On request, it can also be insulated to reduce heat loss, resulting in a considerable economic benefit.

GAS- OR DIESEL-FIRED BURNER with automatic ignition and temperature control and monitoring system.

SPRAY BAR with "slide out" opening action and direct control from vehicle cab.

STANDARD SPREADING WIDTH: 4 m. Can be fitted with hydraulic opening and lifting system.

INTERNAL COMBUSTION ENGINE, normal or fitted with silencer, features electric starting.

RECIRCULATION SYSTEM FOR PURGING spraying system with ecological solvent. **EMULSION PUMP**, self-priming gear type.

FEET kit.

Distributor for Italy:



Veneta Tecnologie srl
Via Serenissima, 4
36075 Montebelluna (VI) Italia
Tel. +39 0444 493111
Fax +39 0444 496329
info@venetatecnologie.com
www.venetatecnologie.com

Authorized dealer: